

Convir ST8818 Series Professional Low Cost Handheld Infrared Thermometer

- ◆ Measure temperature of hot or moving objects from a safe distance
- ◆ Easy and safe to use
- ◆ Built -in laser pointer to improve aim
- ◆ Narrow field of view
- ◆ Backlit display with Data Hold
- ◆ °C/°F switchable
- ◆ Fast sampling time
- ◆ Auto-hold and power off
- ◆ Automatic Range Selection and Resolution
- ◆ Max Hold

The Convir ST8818 is a professional, low cost, handheld infrared thermometer with laser sighting and a large backlit LCD display.

The ST8818 measures from -50°C to 200°C with 0.1°C resolution and from 200°C to 550°C with 1°C resolution - the change in resolution takes place automatically. It also offers a superior 12:1 field of view, which helps to minimise errors by producing a small diameter measurement area.

It has a MAX HOLD facility, which is very useful for finding and measuring hot spots.

The emissivity setting is fixed at 0.95, making the ST8818 ideal for most organic materials and non-shiny (painted, corroded or anodised) metals.

Readings can be taken in °C or °F, and when the trigger is released the last measurement is held for 7 seconds before the unit automatically turns off.

This rugged unit will operate in ambient temperatures from 0°C to 50°C and is powered by a standard PP3 9 V battery.

Elektro-Trading sp. z o.o.

44-109 Gliwice, ul.Mechanikow 9
 Fax: +48 (0-32) 734-55-70
 Tel: +48 (0-32) 734-55-72
 E-mail: et@elektro-trading.com.pl
 http://www.elektro-trading.com.pl



ST8818

Temperature Range (Automatic selection 0.1°C/1°C)		Resolution	Accuracy
-50.0°C to 200.0°C	-50.0°C to -20.0°C	0.1°C	±5°C
	-20.0°C to 200.0°C		2% or ±2°C
200°C to 550°C		1°C	2% or ±2°C

Temperature Range (Automatic selection 0.1°F/1°F)		Resolution	Accuracy
-58.0°F to 200.0°F	-58.0°F to -4.0°F	0.1°F	±9°F
	-4.0°F to 200.0°F		2% or ±4°F
200°F to 1022°F	1°F	1°F	2% or ±4°F

Note: 1. Accuracy is given at 18°C to 28°C (64°F to 82°F), less than 80% RH 2. Accuracy specified is for emissivity of 0.95

GENERAL SPECIFICATIONS

Display	3.5 digit (1999 count) LCD with backlighting
Sample Rate	1 second (approx.)
Emissivity	Fixed at 0.95
Field-of-view	12:1
Spectral Range	6 to 14 µm
Power Off	Automatic shut off after 7 seconds
Ambient Temp. Range	0°C to 50°C (32°F to 122°F)
Relative Humidity	Max. 80% RH
Power	PP3 9 V battery
Weight	200 g
Dimensions	225 x 56 x 69 mm

DISTANCE (D) TO SPOT SIZE (S)

